

APILADOR SEMI ELECTRICO AUTOTRANSPORTABLE MODELO SM-1016ATU



Imagen referencial

Performance	Maximum load capacity	kg	1000	
	Load center	mm	450	
	Maximum lifting height	mm	800/1100/1300/1500/1800	
	Lifting speed (without load)	mm/s	65	
	Lifting speed(with load)	mm/s	35	
	Lowered speed (without load)	mm/s	65	
	Lowered speed(with load)	mm/s	35	
Dimensions	Overall length of frame	mm	1560	
	Overall width of frame	mm	913	
	Mast lowered height	mm	1150/1450/1650/1850/2156	
	Max height(mast lifted with backrest)	mm	2385/2685/2885/3085/3385	
	Wheelbase	mm	845	
	Fork length	mm	1180	
	Fork outside width	mm	580/626	
	Fork inside width	mm	236	
	Fork thickness	mm	70	
	width of theoretical minimum aisle for right-angle stacking (1200x1000)	mm	1200	
	Min frounf height	mm	32	
	Fork lowered height	mm	90	
	Minimum turning radius	mm	1000	
	Tire	Front wheel	mm	80x50
		Hoist motor type		
Rated output		kw	1.2	
Battery	Battery Type			
	Voltage	V	12	
	Capacity	AH	45	